

PHT Sanitary Ultrafiltration Spiral-Wound Element: VT (PES 3kDa)

Synder Filtration's PHT Series of Ultrafiltration

Elements offer exceptional physical and chemical durability, in the same wide range of MWCO's as our standard UF elements. Contact us today to learn more about our complete line of membrane products and services.

PHT SERIES BENEFITS

- Conforms to 3-A, FDA, and USDA sanitary standards
- Elimination of chlorine during CIP with hot sanitation
- High resistance to pH, temperature, & fouling
- Customizable dimensions for unique housings

RECOMMENDED OPERATING PARAMETERS

Operating Parameters	
Maximum Temperature	60°C (140°F)
pH Range @ Max Temperature	2-10
pH Range @ Ambient Temperature	2-10.5

Pressure	PSI	Bar
Max Inlet Pressure	120	8.3
Min Outlet Pressure	10	0.7
Max Differential Pressure per Element	18	1.2
Max Permeate Backpressure	5	0.3

Note: Soft start on boost pumps required to minimize pressure/flow shocks to elements.

Cleaning Parameters	
Maximum Temperature (Short term <30min)	85°C (185°F)
pH Range @ Max Temperature	2-11
pH Range @ Ambient Temperature	2-12.5

Chlorine	Norm ppm	Max ppm
Free Chlorine During Operation	0	<0.1
Chlorine During CIP at pH10.8-11.0 and 50°C	150	180

Note: Maximum chlorine exposure for all elements is 30 minutes per day at pH and temperature conditions listed above.

Dairy Product Total Solids Limits	Feed Spacer (in mils)			
	31	46	65	80
Sweet Whey Max. T.S.	15	25	28	30
Acid Whey Max. T.S.	15	24	26	28
Skim Milk Max. T.S.	14	24	26	28
Whole Milk Max. T.S.	15	30	33	35

Note: Trials should be made to determine temperature and viscosity effects.



COMMON APPLICATIONS

- Antibiotic concentration
- Protein & polypeptide concentration

CONTACT US



4941 Allison Parkway
 Vacaville, CA 95688, USA
 Phone: 1 (707) 451-6060
 Fax: 1 (707) 451-6064
 Email: sales@synderfiltration.com

All inquiries will be responded to by a Synder employee personally within 24 hours.



ELEMENT DIMENSIONS


Element	Model No.	Diameter (B) in	Length (A) in	P.W.T. ID
1.8"	1812F	1.8	12	0.63
	2519	2.5	19.25	0.63
2.5"	2540F	2.5	40	0.63
	2540M*	2.5	38	0.75
3.8"	3838	3.8	38	0.83
	3838.75	3.8	38.75	0.83
	3850	3.8	50	0.83
	3938.75	4.0	38.75	0.63
	4333	4.3	33	0.83
4.3"	4335	4.3	35	0.83
	4335.5	4.3	35.5	0.83
	4336	4.3	36	0.83
	4338	4.3	38	0.83
	5.8"	5838	5.8	38
6.3"	6338	6.3	38	1.14
	6324	6.3	24	1.14
6.4"	6438	6.4	38	1.14
	6424	6.4	24	1.14
7.8"	7838	7.8	38	1.14
	7824	7.8	24	1.14
8"	8038	8.0	38	1.14
	8040	8.0	40	1.14
	8238	8.2	38	1.14
	8240	8.2	40	1.14
	8338	8.3	38	1.14
	8340	8.3	40	1.14
9.8"	9838	9.8	38	1.14
10"	10338	10.3	38	1.14

*1" permeate tube extensions (0.75" OD)

RECOMMENDED ELEMENT CROSS FLOW RATE

Element		Feed Spacer (in mils)				
		24	31	46	65	80
1.8"	m ³ /hr	1	1	1	2	2
	gpm	4	5	6	7	7
2.5"	m ³ /hr	2	2	3	3	3
	gpm	9	10	11	12	13
3.8"	m ³ /hr	5	6	7	8	8
	gpm	22	25	29	33	35
4.3"	m ³ /hr	6	7	9	10	10
	gpm	29	32	38	44	46
5.8"	m ³ /hr	12	13	16	18	19
	gpm	51	59	69	78	83
6.3"	m ³ /hr	15	17	20	22	24
	gpm	65	74	88	99	105
8"	m ³ /hr	21	24	29	33	35
	gpm	94	107	128	143	154
10"	m ³ /hr	42	48	57	64	68
	gpm	184	213	250	283	299

The recommended cross flow rate will be subject to differential pressure limitations and specific applications. Please consult Synder Filtration if additional information is needed.



MEMBRANE AREA (SQ. FT.)

Element	Model No.	Feed Spacer (in mils)					
		24	31	46	65	80	
1.8"	1812F	N/A	3.6	N/A	N/A	N/A	
	2519	15	13	10	N/A	N/A	
2.5"	2540F	34	29	22	N/A	N/A	
	2540M	35	30	23	N/A	N/A	
	3838	85	72	58	46	38	
	3838.75	86	74	59	47	39	
3.8"	3850	100	84	70	52	46	
	3938.75	102	89	69	53	47	
	4333	99	86	66	53	44	
	4335	105	91	71	56	47	
	4335.5	107	93	72	57	48	
4.3"	4336	108	94	73	58	49	
	4338	115	100	77	62	52	
	5.8"	5838	210	184	147	114	96
	6.3"	6324	150	134	107	83	70
6.4"	6338	246	220	176	136	115	
	6424	157	140	112	83	74	
	6438	258	230	184	136	122	
	7.8"	7824	242	210	166	132	110
7.8"	7838	396	344	273	216	180	
	8038	414	368	287	225	189	
	8040	414	368	287	225	189	
	8238	441	384	302	238	201	
	8240	441	384	302	238	201	
	8338	450	400	311	245	207	
9.8"	9838	N/A	564	440	351	296	
	10338	N/A	620	492	386	326	

TECHNICAL NOTES

For element sizes not listed, please call or email Synder Filtration for details. We can design an element to fit your exact needs – just specify the element outer diameter (OD) or vessel/housing inner diameter (ID), element inner diameter (ID), and length. Elements are also available with or without a controlled bypass tail. Additional feed spacers are also available. Trials should be conducted to determine optimal application conditions.

ELEMENT DESCRIPTIONS

Model No.	OD (in.)	L (in.)	ID* (in.)	Weight (lb)	Weight (kg)
1812F	1.8	12	0.63	1.0	0.5
2519	2.5	19.25	0.63	2	0.9
2540F	2.5	40	0.63	4	1.8
2540M*	2.5	38	0.75	4	1.8
3838	3.8	38	0.83	10	4.5
3838.75	3.8	38.75	0.83	10	4.5
3850	3.8	50	0.83	13	5.9
3938.75	4.0	38.75	0.63	10	4.5
4333	4.3	33	0.83	11	5.0
4335	4.3	35	0.83	11	5.2
4335.5	4.3	35.5	0.83	11	5.2
4336	4.3	36	0.83	11	5.2
4338	4.3	38	0.83	12	5.4
5838	5.8	38	1.14	15	7
6338	6.3	38	1.14	16	7
6324	6.3	24	1.14	17	7.7
6438	6.4	38	1.14	29	13.2
6424	6.4	24	1.14	18	8.2
7838	7.8	38	1.14	40	18.2
7824	7.8	24	1.14	26	11.8
8038	8.0	38	1.14	38	17.2
8040	8.0	40	1.14	39	17.7
8238	8.2	38	1.14	38	17.2
8240	8.2	40	1.14	40	18
8338	8.3	38	1.14	40	18
8340	8.3	40	1.14	40	18
9838	9.8	38	1.14	42	19.1
10338	10.3	38	1.14	50	22.7

*1" permeate tube extensions (0.75" OD)

NOTE: Different diameters are available. Please specify your requirements when ordering. Specifications are subject to change without notice.