

Standard High pH/Temperature Cleaning Guideline

The following procedure is a general guideline for the cleaning/sanitation of PHT spiral elements for most food and dairy applications. PHT elements have the advantage of hot sanitation while eliminating the use of chlorine for sanitation. In addition, the cleaning time for PHT elements is typically 2-4 times faster than traditional cleaning procedures. Do not use chlorine, peroxide, or any other oxidizer.

Depending on individual process streams, equipment and process time some variations in cleaning procedures may be required for optimal cleaning results. Please consult a qualified chemical supplier for application specific cleaning regimes.

Improper cleaning sequence, chemical concentration or abnormal temperatures/pH/ pressure profiles can significantly reduce membrane life and possibly void any warranties offered on the element(s). If you have ANY questions or concerns about your cleaning regime, please contact Synder Filtration immediately.

Concentrate Displacement and Initial Flush

1. Flush the remaining concentrate in the system back to the concentrate tank or to drain.
2. Using clean water heated to 122°F (50°C), adequately flush the system in non-recirculation mode to remove any remaining build-up. The retentate and permeate should appear to be clean after this step.
3. Perform a complete Clean-In-Place (CIP) immediately after the initial flush per the following.

Caustic Wash

1. Circulate hot clean water (185°F or 85°C) through the system under standard pressure and flow parameters.
2. Add caustic SLOWLY to achieve a pH of 12.5. **DO NOT EXCEED pH 12.5.**
3. Circulate caustic solution for 10 minutes.
4. Flush the system to drain with clean, warm water (same temperature as before).

Acid Wash

1. Circulate warm clean water 122°F (50°C) through the system under standard pressure and flow parameters.
2. Add a sufficient amount of acid SLOWLY to achieve a pH of 2.0-2.2.
3. Circulate caustic solution for 20 minutes.

High Temperature/pH Sanitation

1. Circulate warm clean water 158°F (70°C) through the system under standard pressure and flow parameters.
2. Add caustic SLOWLY to achieve a pH of 12.5. **DO NOT EXCEED pH 12.5.**
3. Circulate the caustic solution for 30 minutes.
4. Flush the system to drain with clean, warm water 122°F (50°C).

Synder Filtration believes the above information and data herein to be accurate. However, said information is offered in good faith, but without guarantee of results since the conditions and methods used are beyond Synder Filtration's control. Synder Filtration assumes no liability as to the application of the previously mentioned data.